



Cannulated Cancellous Screw



Wkręty kaniulowane fi 4,5mm, L = 10-90 mm, częściowo gwintowany, samowiercący, gniazdo sześciokątne

732SD		Cannulated Cancellous Screw 4.5 mm, Partially threaded , Self Tapping and self drilling	
kod	CODES	Length (mm)	długość
stal	Titanium		
732SD.010	732SD.010T	Length 10mm	
732SD.015	732SD.015T	Length 15mm	
732SD.020	732SD.020T	Length 20mm	
732SD.025	732SD.025T	Length 25mm	
732SD.030	732SD.030T	Length 30mm	
732SD.035	732SD.035T	Length 35mm	
732SD.040	732SD.040T	Length 40mm	
732SD.045	732SD.045T	Length 45mm	
732SD.050	732SD.050T	Length 50mm	
732SD.055	732SD.055T	Length 55mm	
732SD.060	732SD.060T	Length 60mm	
732SD.065	732SD.065T	Length 65mm	
732SD.070	732SD.070T	Length 70mm	
732SD.075	732SD.075T	Length 75mm	
732SD.080	732SD.080T	Length 80mm	
732SD.085	732SD.085T	Length 85mm	
732SD.090	732SD.090T	Length 90mm	