


BoxLED Side Plus

LED modules for light advertising and backlighting



Product name	GTIN (EAN)	W	V	A	W MODULE	lm	lm/w	K	Ra
BX06SA-W4F-830	4008321828767	115.2	24	4.8	3.6	7680	67	3000	> 80
BX06SA-W4F-765	4008321828606	115.2	24	4.8	3.6	9280	81	6500	> 70

Product name	Ta	IP	Ø d [mm]	l [mm]	b [mm]	h [mm]		lm CHAIN	MODULES/ CHAIN
BX06SA-W4F-830	-25...95	IP66	not relevant	9600 ¹	35	20.6	3000	7680	32
BX06SA-W4F-765	-25...95	IP66	not relevant	9600 ¹	35	20.6	6500	9280	32

Product name		Im MODUL	°	t _{in}		cd		
BX06SA-W4F-830	6	240	12 ° x 67	50000	Yes	not relevant	A	1
BX06SA-W4F-765	6	290	12 ° x 67	50000	Yes	not relevant	A	1

¹ Maximum LED pitch 300 mm

PRODUCT FEATURES

- Chain of 32 linear LED modules
- Connected with flexible cables
- Maximum length of one chain: 9.60 m
- Type of protection (modules): IP66
- Special robust encapsulation
- Fully integrated heat sink

PRODUCT BENEFITS

- Modules are compatible with the BoxLED mounting profile
- Uniform illumination thanks to optimized elliptical lenses
- Several options for quick and simple mounting: bolting or snap-in
- Excellent module efficacy
- Very long lifetime

AREAS OF APPLICATION

- Signage and illuminated advertising
- Illumination of single and double-sided light boxes
- Permanent outdoor use in enclosed light boxes

EQUIPMENT / ACCESSORIES

- Several types of OPTOTRONIC 24 V power supplies available