























Obiekt: Przedszkole w Katowicach									MKT	
Treść rys.: Zbrojenie płyty dachu										
2021-06-28		SPECYFIKACJA DO RYSUNKU NR:			KAT-PW-K-09				1 / 3	
ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	Φ	Φ	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			A-0	A-IIIIN		I	na 1 el.			
1	2	3	4	5	6	7	8	9	10	11
Szczegół "AT"	9		-	12	108.3 mb	-	-	108.3	96.2	Σ= 351.7
	42		-	10	282.0	-	83	234.1	144.3	
	51		-	10	180.5 mb	-	-	180.5	111.3	
Zbrojenie dodatkowe	10		-	12	88.0	-	452	397.8	353.1	Σ= 522.7
	51		-	10	275.0 mb	-	-	275.0	169.5	
Zbrojenie dolne płyty 1. piętra.	7		-	12	195.0	-	6	11.7	10.4	Σ= 22.1
	8		-	12	165.0	-	8	13.2	11.7	
Zbrojenie dolne płyty dachu.	5		-	12	300.0	-	3	9.0	8.0	Σ= 1150.2
	6		-	12	275.0	-	2	5.5	4.9	
	11		-	10	1200.0	-	6	72.0	44.4	
	12		-	10	965.0	-	6	57.9	35.7	
	13		-	10	900.0	-	28	252.0	155.4	
	14		-	10	890.0	-	24	213.6	131.7	
	15		-	10	885.0	-	31	274.4	169.1	
	16		-	10	750.0	-	28	210.0	129.5	
	18		-	10	690.0	-	9	62.1	38.3	
	21		-	10	600.0	-	22	132.0	81.4	
	22		-	10	575.0	-	22	126.5	78.0	
	23		-	10	570.0	-	5	28.5	17.6	
	24		-	10	565.0	-	22	124.3	76.6	
	25		-	10	550.0	-	53	291.5	179.7	
KAT-PW-K-09_specyfikacja									 Adelante Solutions © 2014 - 2021	















ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	Φ	Φ	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			A-0	A-IIIIN		na 1 el.	na Σ el.			
1	2	3	4	5	6	7	8	9	10	11
Zbrojenie dolne płyty dachu.	26		-	10	540.0	-	22	118.8	73.2	$\Sigma=$ 582.8
	27		-	10	480.0	-	28	134.4	82.9	
	28		-	10	455.0	-	39	177.5	109.4	
	29		-	10	430.0	-	28	120.4	74.2	
	35		-	10	335.0	-	5	16.8	10.3	
	39		-	10	310.0	-	51	158.1	97.5	
	40		-	10	300.0	-	32	96.0	59.2	
	44		-	10	260.0	-	44	114.4	70.5	
	52		-	10	65.0	-	9	5.9	3.6	
	53	Kształt wg rysunku	-	8	120.0	-	4	4.8	1.9	
Zbrojenie górne płyty dachu.	1		-	12	850.0	-	130	1105.0	981.0	$\Sigma=$ 1705.6
	2	Kształt wg rysunku	-	12	700.0	-	3	21.0	18.6	
	3	Kształt wg rysunku	-	12	400.0	-	2	8.0	7.1	
	4		-	12	400.0	-	8	32.0	28.4	
	13		-	10	900.0	-	10	90.0	55.5	
	17		-	10	700.0	-	17	119.0	73.4	
	19		-	10	645.0	-	12	77.4	47.7	
	20		-	10	610.0	-	58	353.8	218.1	
	25		-	10	550.0	-	16	88.0	54.3	
	30		-	10	420.0	-	19	79.8	49.2	
	31		-	10	405.0	-	14	56.7	35.0	
	32		-	10	400.0	-	36	144.0	88.8	
	33		-	10	375.0	-	21	78.8	48.6	

2021-06-28

SPECYFIKACJA DO RYSUNKU NR:

KAT-PW-K-09

3 / 3

ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	Φ	Φ	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			A-0	A-IIIIN		na 1 el.	na Σ el.			
1	2	3	4	5	6	7	8	9	10	11
Zbrojenie górne płyty dachu.	34		-	10	350.0	-	52	182.0	112.2	$\Sigma = 635.9$
	36		-	10	330.0	-	11	36.3	22.4	
	37		-	10	330.0	-	18	59.4	36.6	
	38		-	10	320.0	-	34	108.8	67.1	
	40		-	10	300.0	-	68	204.0	125.8	
	41		-	10	300.0	-	20	60.0	37.0	
	43		-	10	270.0	-	8	21.6	13.3	
	45		-	10	250.0	-	27	67.5	41.6	
	46		-	10	250.0	-	11	27.5	17.0	
	47		-	10	250.0	-	40	100.0	61.7	
	48		-	10	220.0	-	9	19.8	12.2	
	49		-	10	220.0	-	37	81.4	50.2	
	50		-	10	220.0	-	26	57.2	35.3	
	52		-	10	65.0	-	9	5.9	3.6	