



GRUN N LED-SE

Naświetlacz LED SMD
z czujnikiem ruchu /
LED SMD floodlight
with a motion detector


IP44




● GRUN N LED-10-B-SE



● GRUN N LED-30-B-SE



● GRUN N LED-20-B-SE



● GRUN N LED-50-B-SE

obudowa: stop aluminium / szyba ochronna: szkło hartowane
/ wysięgnik: metal żelazny /
casing: aluminum alloy / protective pane: tempered glass /
extension arm: ferrous metal



NAZWA / NAME	KOD / CODE	MOC / POWER	TEMPERATURA BARWOWA TC (K) / COLOUR TEMPERATURE	STRUMIEŃ ŚWIETŁNY (LM) / LUMINOUS FLUX	MONTAŻ / ASSEMBLY	ZAKRES DOPUSZCZALNEJ TEMPERATURY OTOCZENIA / ALLOWABLE AMBIENT TEMPERATURE RANGE
220-240V~; 50/60Hz						
GRUN N LED-10-B-SE	30324	10W	4000	700		-20+35°C Rys nr 16
GRUN N LED-20-B-SE	30325	20W		1400		
GRUN N LED-30-B-SE	30326	30W		2100		
GRUN N LED-50-B-SE	30327	50W		3500		