


better together

February 1st 2018

Road Reinforcement



Performance testing anti-cracking interlayers

Frederik Vervaecke

Zwevegem

February 2018

Confidentiality

This document remains the exclusive property of NV Bekaert SA.

Communication thereof is wholly confidential and does not extend beyond the technical staff of the addressee, who is not authorized to duplicate this document nor to make known to a third party any contents thereof.

NV Bekaert SA is exclusively entitled to apply for a patent for any patentable element contained in this document.

NV Bekaert SA disclaims all liability which may arise out of the putting into use of the information contained in this document, provided it did not assume control thereof. It also disclaims all liability for infringements of industrial property rights which may arise out of the putting into use of the information contained in this document.

All the information contained in this document is based on reasonable research, but does not guarantee any result.

Laboratory testing

Standardized testing of anti-cracking interlayers for asphalt:

Properties interlayer



Tensile testing



Bitumen retention test



Performance anti-cracking interlayer

Nothing standardized

Laboratory testing

Big variety of performance tests of anti-cracking interlayers:

1. Static testing : 3- or 4-pt bending test:



Only first part of the curve
was recorded & investigated

Pro:

- fast test;
- Simple setup;
- Relative large samples;

Contra:

- Relevant for reality?
- Not straight forward interpretation;

A.G. Kneepkens, M Verweij, 2015, "Gewapende feiten over asfaltwapening", Civielm techniek Nr , 30-33
E. Pasquini, M. Bocci, G. Ferrotti, & F. Canestrari, éà&,"Laboratory characterisation and field validation of geogrid-reinforced asphalt pavements", Road Mat. & Pav. Design, 14:1, 17-35.

Laboratory testing

Big variety of performance tests of anti-cracking interlayers:

2. Cyclic bending tests:

Several setups and research groups have there own test (Nottingham, Santander, Teheran, Italy,...)

- D.Z. Zamora-Barraza, M.A. Calzada-Pérez, D. Castro-Fresno, A. Vega-Zamanillo, 2011, "Evaluation of anti-reflective cracking systems using geosynthetics in the interlayer zone, *Geotextiles & geomembranes* 29, 130-136.
- J. Norambuena-Contreras, & I Gonzalez-Torre, 2015, "Influence of geosynthetic type on retarding cracking in asphalt pavements", *Construction & Building Materials* 78, 412-429.
- I. Gonzalez-Torre, M Calzada-Perez, A. Vega-Zamanillo, D. Castro-Fresno, 2015, "Evaluation of reflective cracking in pavements using a new procedure that combine loads with different frequencies", *Construction & Building Materials* 75, 368-374.
- G. Ferrotti, F. Canestrari, A. Virgili, A. Grilli, "A strategic laboratory approach for the performance investigation of geogrids in flexible pavements," *Construction and Building Materials* 25 (2011) 2343-2348
- A. Virgili, F. Canestrari, A. Grilli, F.A. Santagata, "Repeated load test on bituminous systems reinforced by geosynthetics", *Geotextiles and Geomembranes* 27 (2009) 187-195
- S. Fallah & A. Khodaii, 2015, "Reinforcing overlay to reduce reflection cracking: an experimental investigation", *Geotextiles & Geomembranes* 43, 216-227.
- Brown, "An assessment of geogrid use in railways and asphalt applications", Jubilee 2009.
- Brown, Brunton, Hughes & Bodrick, 1985, "Polymer grid reinforcement of asphalt", *Journal as Asphalt Technology*, 54, 18-41.
- Brown Thom, & Sanders, 2001, "A study of grid reinforced asphalt to combat reflection cracking", *Journal of Asphalt Paving Technology*; 70, 543-570.



Laboratory testing

Big variety of performance tests of anti-cracking interlayers:

2. Cyclic bending tests:

Several setups and research groups have there own test (Nottingham, Santander, Teheran, Italy,...)

Example:



Pro:

- Relative simple test setup;
- Relative large samples;

Contra:

- Long test
- Spread on results (fatigue)
- Not straight forward interpretation


Laboratory testing

Big variety of performance tests of anti-cracking interlayers:

3. Thermal movement test:

Several setups and research groups have there own test (Nottingham, Texas, Belgium, ...)

Example:



Contra:

- Long test
- Spread on results (fatigue)
- Special setup is needed

Pro:

- Realistic seasonal movement;
- Relative large samples are possible;

J. Li, J. Oh, B Naik, G.S. Simate, L.F. Walabitu, "Laboratory characterization of cracking-resistance potential of asphalt mixes using overlay tester", Con. & Build, mat. 70 (2014), 130-140;
L.F. Walubita, A.N.M. Faruk, J. Zhang, X. Hu, "Characterizing the cracking & fracture properties of geosynthetic interlayer reinforced HMA samples using the Overlay Tester (OT)", Con. & Build, mat. 93 (2015), 695-702;
F. Zhou, S. Hu, D. Chen, T. Scullion, "Overlay tester: A simple performance test for fatigue cracking", TRB 2007 Annual Meeting
R. Lytton, "Use of geotextiles for reinforcement and strain relief in asphalt concrete", Geotextiles and Geomembranes 8 (1989) 217-237

Laboratory testing

Big variety of performance tests of anti-cracking interlayers:

4. Large scale fatigue testing:

Several setups and research groups have there own test (France, Spain, Switzerland, Netherlands, ...)

Example:



Contra:

- Long test
- Spread on results (fatigue)
- Special setup is needed
- Complete road structure not only the asphalt/interlayer composite
- Very expensive


Pro:

- Realistic situation
- Entire road structure

<https://www.hbm.com/en/5949/cedex-test-track-accelerated-pavement-testing/>


Important parameters for testing anti-cracking interlayers:

- Testing the composite (interlayer, tack coat & asphalt) as it is used in the application;
- As reflective cracking is a fatigue behavior, it is important to perform cyclic testing;



- Sample dimensions must be adapted to the dimensions of the anti-cracking interlayer;
- Details of asphalt, tack coat, base layer need to be kept unchanged;




Thermal plate test :



- ⇨ specimen on bed of steel balls for free horizontal displacement;
- ⇨ climate chamber conditioned at -10°C ;
- ⇨ slow cyclic opening & closing joint (1mm) by contraction & expansion of loading frame;
- ⇨ Observations:
 - crack initiation & development (by pictures);
 - applied force;
 - opening joint (0-1mm);
 - relative displacement in overlay (2cm above joint).


* Operating procedure for thermal cracking test, Belgian Road Research Centre, oct 2010.

Thermal plate test :

reference - no interlayer 	Fortifix® 1-O 	Glas grid 35x35 
+ 300g/m ² tack coat	(38x50)kN/m (3100x4400)kN/m + 300g/m ² tack coat	(70x100)kN/m (2800x4000)kN/m + 300g/m ² tack coat


* All tests were done in the same period to make sure there are no differences in used materials.

Thermal plate test :



	F _{max} (kN)	Crack initiation		End of test		Remarks
		cycles	time (h)	cycles	time (h)	
Reference	8	1	2	5	10	crack
Fortifix	9	Na	Na	Na	130	no cracks
	8,7	35	126	35	126	delamination
	9,5	15	42	24	90	crack
Glas grid	9,6	8	32	11	48	delamination + crack
	9,3	28	108	28	108	delamination

Thermal plate test :



strength new steel grid = $\frac{1}{2}$ x glas grid & EA is equal

⇒ **similar/better performance (15-50%)**

*Preliminary &
unpublished results*

What about FF1 & carbophalt?

• Reference	no interlayer	tackcoat	300g/m ²
• SAMI	SAMI	PMB	2kg/m ²
• Carbon/glas grid	(120x200)kN/m	tackcoat	300g/m ²
	(4 000x12 000)kN/m		
• FF1-C	(42x54)kN/m	tackcoat	500g/m ² (1 sample)
	(3 000x4 400)kN/m		700g/m ² (2 samples)

To be submitted for publication in 2019



*Preliminary &
unpublished results*

What about FF1 & carbophalt?



	Tack coat g/m ²	F _{max} (kN)	Crack initiation cycles	Crack @ top asphalt cycles	F _{end} (kN)	Remarks
Reference	300	8	1	5	0,04	crack
SAMI	2000	7	1	2	0,04	cracks
	2000	9	1	3	0,08	delamination + crack
Carbon/glas	300	10,5	2	5	2,6	delamination + crack
	300	10	1	5	4,2	crack
FF1-C	500	11,4	2	30	3,7	crack
	700	11,9	1	20	2,8	crack
	700	12	10	50	5,5	crack (not @surface yet)

To be submitted for publication in 2019





*Preliminary &
unpublished results*

What about FF1 & carbophalt?



*Preliminary &
unpublished results*

What about FF1 & carbophalt?





- ⇒ Both the number of cycles before the end of the test as the maximum force & the force at the end of the test show a significant effect on preventing crack initiation and crack growth.

To be submitted for publication in 2019



*Preliminary &
unpublished results*

What about FF1 & carbophalt?



Athough FF = 1/4 x carbon grid & EA FF = 1/3 x carbon grid

⇒ **better performance based on crack propagation & Force take-up**

To be submitted for publication in 2019




How can this be explained?


1. Adhesion to overlay :



Interlocking 3D structure ensures anchorage;



2. Adhesion existing surface & overlay:



Shear test:

limited reduction surface by steel compared to glass

⇒ *adhesion interface is less influenced*

To be submitted for publication in 2019



Road Reinforcement

February 1st 2018



better together