



chodnika
SKALA 1:25



The diagram illustrates a cross-section of a road edge. On the left, the 'proj. nawierzchnia zjazd publiczny' (projected surface of the public road) is shown with a red hatched pattern. On the right, the 'istniejąca nawierzchnia jezdni asfaltowa drogi wojewódzkiej DW210' (existing asphalt surface of the provincial road DW210) is shown with an orange hatched pattern. A vertical dimension of 15 indicates the height of the 'krawężnik' (curb). The curb is shown with three elevation points: +0,03, +0,02, and +0,00. A note indicates that the gap ('szczelinę') should be filled with bituminous mass. The left side is labeled 'Zgodny z proj. pochyleniem podłużnym zjazdu' (Consistent with the projected longitudinal slope of the ramp), and the right side is labeled 'Zgodny z spadkiem istn. jezdni drogi woj.' (Consistent with the existing slope of the road surface).

***Przebudowa pasa drogowego drogi wojewódzkiej DW 210
i drogi gminnej w m. Głobino, gm. Słupsk.***

-
- Figure 1 shows four cross-sectional diagrams of a concrete slab with a steel reinforcement bar. The diagrams are labeled 1, 7, 3, and 5. Each diagram shows the slab thickness, the position of the reinforcement bar, and the dimensions of the concrete cover and the reinforcement bar itself. The dimensions are given in millimeters (mm).
- Diagram 1:** Slab thickness is 30 mm. The reinforcement bar is positioned 10 mm from the bottom. The concrete cover on the top is 515 mm. The concrete cover on the bottom is 10 mm. The reinforcement bar has a diameter of 15 mm. The width of the slab is 30 mm.
 - Diagram 7:** Slab thickness is 35 mm. The reinforcement bar is positioned 10 mm from the bottom. The concrete cover on the top is 522 mm. The concrete cover on the bottom is 10 mm. The reinforcement bar has a diameter of 15 mm. The width of the slab is 30 mm.
 - Diagram 3:** Slab thickness is 30 mm. The reinforcement bar is positioned 10 mm from the bottom. The concrete cover on the top is 317 mm. The concrete cover on the bottom is 10 mm. The reinforcement bar has a diameter of 15 mm. The width of the slab is 21 mm.
 - Diagram 5:** Slab thickness is 26 mm. The reinforcement bar is positioned 10 mm from the bottom. The concrete cover on the top is 522 mm. The concrete cover on the bottom is 10 mm. The reinforcement bar has a diameter of 15 mm. The width of the slab is 35 mm.

| | | | | |
|--|---|-----------------------|--|---|
| <h1 style="text-align: center;">Usługi Projektowe Tomasz Ofierzyński</h1> <p style="text-align: center;">ul. Wydmowa 6, 75-229 Koszalin, tel.: 505 073 316, NIP 669-216-58-83, e-mail: drogi@sykoma.com.pl</p> | | | |  |
| Inwestor | Gmina Słupsk, 76-200 Słupsk, ul. Sportowa 34 | | | SKALA 1:25 |
| Obiekt | Przebudowa pasa drogowego DW 210 i drogi gminnej w m. Globino, gm.Słupsk. | | | |
| Nazwa rys. | PRZEKROJE KONSTRUKCYJNE - CHARAKTERYSTYCZNE | | | RYSUNEK NR 4 |
| Projektował | inż. Błażej Pacholek | Upr. ZAP/0087/PWOD/15 | | DATA grudzień 2021 |
| Opracował | inż. Tomasz Ofierzyński | | | |
| | | | | |