






































Obiekt: Centrum Aktywności Lokalnej w Mszczonowie									MKT	
Treść rys.: Zbrojenie detali płyty 2 piętra										
2022-08-31		SPECYFIKACJA DO RYSUNKU NR:			MSZ-PW-K04-ark.4				1 / 4	
ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	F	F	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			A-0	A-IIIIN		I	na 1 el.			
1	2	3	4	5	6	7	8	9	10	11
Belka "B1.1"	30	Kształt wg rysunku	-	12	183.5	-	9	16.5	14.7	Σ= 39.7
	35	7.5 mb	-	12	7.5 mb	-	-	7.5	6.7	
	39	11  17	-	10	129.0	-	16	20.6	12.7	
	43	9  16	-	8	160.0	-	9	14.4	5.7	
Belka "B1.2"	21	 16	-	12	367.4	-	20	73.5	65.2	Σ= 152.9
	27	Kształt wg rysunku	-	12	225.5	-	20	45.1	40.0	
	35	18.66 mb	-	12	18.7 mb	-	-	18.7	16.6	
	39	11  17	-	10	129.0	-	39	50.3	31.0	
Belka "B2"	28	Kształt wg rysunku	-	12	223.5	-	63	140.8	125.0	Σ= 409.5
	35	82.08 mb	-	12	82.1 mb	-	-	82.1	72.9	
	36	11  23	-	10	161.0	-	125	201.3	124.1	
	41	9  18	-	8	176.0	-	126	221.8	87.5	
Belka "B3.1"	35	40.52 mb	-	12	40.5 mb	-	-	40.5	36.0	Σ= 90.1
	41	9  18	-	8	176.0	-	78	137.3	54.2	
Belka "B3.2"	35	43.72 mb	-	12	43.7 mb	-	-	43.7	38.8	Σ= 155.5
	41	9  18	-	8	176.0	-	168	295.7	116.7	
Belka "B4.1"	35	22 mb	-	12	22.0 mb	-	-	22.0	19.5	Σ= 34.5
	42	9  16	-	8	172.0	-	22	37.8	14.9	
MSZ-PW-K04-ark.4_spec						 Adelante Solutions © 2014 - 2022				

Obiekt: Centrum Aktywności Lokalnej w Mszczonowie									MKT	
Treść rys.: Zbrojenie detali płyty 2 piętra										
2022-08-31		SPECYFIKACJA DO RYSUNKU NR:			MSZ-PW-K04-ark.4				2 / 4	
ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	F	F	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			A-0	A-IIIIN		I	na 1 el.			
1	2	3	4	5	6	7	8	9	10	11
Belka "B4.2"	35		-	12	22.0 mb	-	-	22.0	19.5	Σ= 48.7
	42		-	8	172.0	-	43	74.0	29.2	
Dozbrojenie otworów	40		-	10	121.0	-	13	15.7	9.7	Σ= 9.7
Szczegół "Ł1"	34		-	12	145.0	-	18	26.1	23.2	Σ= 23.2
Szczegół "Ł2"	32		-	12	175.0	-	52	91.0	80.8	Σ= 80.8
Oparcie "Ns1"	35		-	12	158.9 mb	-	-	158.9	141.1	Σ= 429.0
	37		-	10	145.0	-	322	466.9	287.9	
Oparcie "Ns2"	35		-	12	196.4 mb	-	-	196.4	174.4	Σ= 500.8
	38		-	10	133.0	-	398	529.3	326.4	
Detal "X1.1"	35		-	12	254.2 mb	-	-	254.2	225.7	Σ= 225.7
MSZ-PW-K04-ark.4_spec						 Adelante Solutions © 2014 - 2022				

Obiekt: Centrum Aktywności Lokalnej w Mszczonowie									MKT	
Treść rys.: Zbrojenie detali płyty 2 piętra										
2022-08-31		SPECYFIKACJA DO RYSUNKU NR:			MSZ-PW-K04-ark.4				3 / 4	
ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	F	F	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			A-0	A-IIIIN		I	na 1 el.			
1	2	3	4	5	6	7	8	9	10	11
Detail "X1.2"	35		-	12	10.7 mb	-	-	10.7	9.5	Σ= 9.5
Detail "X2.1" szt. 4	33		-	12	145.0	2	8	11.6	10.3	Σ= 10.3
Detail "X2.2" szt. 4	33		-	12	145.0	2	8	11.6	10.3	Σ= 10.3
szt. 19 Detail "X3.1"	19		-	12	1180.0	2	38	448.4	398.1	Σ= 515.1
	45		-	8	39.0	40	760	296.4	117.0	
Detail "X3.2" szt. 7	20		-	12	1078.0	2	14	150.9	134.0	Σ= 173.8
	45		-	8	39.0	37	259	101.0	39.9	
Zbrojenie detali płyty poz.+7.79	1		-	20	1120.0	-	3	33.6	82.9	Σ= 374.5
	2		-	20	505.0	-	3	15.2	37.4	
	3		-	20	500.0	-	4	20.0	49.3	
	4		-	20	470.0	-	3	14.1	34.8	
	5		-	16	990.0	-	2	19.8	31.3	
	6		-	16	745.0	-	4	29.8	47.0	
	7		-	16	740.0	-	4	29.6	46.7	
	8		-	16	715.0	-	4	28.6	45.1	
MSZ-PW-K04-ark.4_spec										
						 Adelante Solutions © 2014 - 2022				

ELEMENT	POZYCJA	SZKIC PRĘTA [cm]	F	F	Długość [cm]	Ilość "n" [szt.]		"n x l" [m]	Ciężar [kg]	Ciężar całk. [kg]
			A-0	A-IIIIN		na 1 el.	na S el.		wg F	S
1	2	3	4	5	6	7	8	9	10	11
Zbrojenie detali płyty poz.+7.79	9		-	16	660.0	-	4	26.4	41.7	Σ= 644.1
	10		-	16	610.0	-	4	24.4	38.5	
	11		-	16	570.0	-	4	22.8	36.0	
	12		-	16	520.0	-	6	31.2	49.2	
	13		-	16	505.0	-	4	20.2	31.9	
	14		-	16	495.0	-	2	9.9	15.6	
	15		-	16	490.0	-	4	19.6	30.9	
	16		-	16	480.0	-	4	19.2	30.3	
	17		-	16	460.0	-	4	18.4	29.0	
	18		-	16	315.0	-	4	12.6	19.9	
	22		-	12	330.0	-	12	39.6	35.2	
	23		-	12	300.0	-	12	36.0	32.0	
	24		-	12	255.0	-	1	2.6	2.3	
	25		-	12	240.0	-	16	38.4	34.1	
	26		-	12	240.0	-	12	28.8	25.6	
	29		-	12	220.0	-	96	211.2	187.5	
	31		-	12	180.0	-	1	1.8	1.6	
	44		-	8	120.0	-	6	7.2	2.8	