Technology

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0.61 inch with MLA (D10)

Image

Colour Light Output 3,100 Lumen- 1,925 Lumen (economy) in accordance with

IDMS15.4

White Light Output 3,100 Lumen - 1,925 Lumen (economy) in accordance with ISO

21118:2012

Resolution Full HD 1080p, 1920 x 1080, 16:9

High Definition Full HD Aspect Ratio 16:9

Contrast Ratio 15,000: 1

Light source Lamp

Lamp UHE, 210 W, 4,500 h durability, 7,500 h durability (economy

mode)

Keystone Correction Auto vertical: ± 30 °, Manual horizontal ± 30 °

Colour Processing 10 Bits

2D Vertical Refresh

Rate 192 Hz - 240 Hz

Colour Reproduction upto 1.07 billion colours

Optical

Projection Ratio 1.02 - 1.23:1

Zoom Manual, Factor: 1.2

Lens Optical

Image Size 30 inches - 300 inches

Projection Distance Wide/Tele 1.35 m - 1.64 m (60 inch screen)

Projection Lens F Number 1.58 - 1.7

Focal Distance 18.2 mm - 29.2 mm

Focus Manual Offset 13.9 : 1

Connectivity

USB Display

Function 2 in 1: Image / Mouse

Interfaces

USB 2.0 Type A, USB 2.0 Type B, Wireless LAN IEEE 802.11b/g/n (WiFi 4), VGA in, HDMI in (2x), Composite in, MHL, Cinch audio in

Epson

iProjection App

Ad-Hoc / Infrastructure

Advanced Features

Security Kensington lock, Security cable hole, Password protection

3D No

2D Colour

Modes Dynamic, Cinema, Bright Cinema

AV mute slide, Automatic keystone correction, Built-in speaker,

Features Horizontal and vertical keystone correction, MHL audio/video interface,

Quick Corner, Split-Screen-Function

Video

Colour

Cinema, Dynamic, Game, Bright Cinema

Modes

General

Energy Use 298 Watt, 219 Watt (economy), 0.2 Watt (standby), On mode power

consumption as defined in JBMS-84 264 Watt

Supply

Voltage

AC 100 V - 240 V, 50 Hz - 60 Hz

Product

dimensions

302 x 252 x 92 mm (Width x Depth x Height)

Product

weight

2.7 kg

Noise Level Normal: 37 dB (A) - Economy: 28 dB (A)

Temperature Operation 5° C - 35° C, Storage -10° C - 60° C

Operation 20% - 80%, Storage 10% - 90%

If the projector is suspended from a ceiling or wall mount and

installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles

Humidity are used for event staging, or where aroma oils are frequently

burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the

projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.

Options Air filter, Soft carry case

Loudspeaker 2 Watt

What's in the Main unit, Power cable, Quick Start Guide, Remote control incl.

box batteries, User manual (CD), Warranty card

Room Type / Gaming, Home Cinema, Home Photo, Sports, Streaming, TV & Box

Application sets

Positioning Ceiling Mounted, Desktop

Colour White